10FEET PALLET DOLLY



Model No.: HD-P011703

10FEET PALLET DOLLY

FEATURES:

- *ULD to handle: LD1/LD3,LD8 container, or any container and pallet with the bottom size 125"x96", 125"x88"and 108"x88".
- *96" side loading.
- *Front swivel castor steering.
- *Brake works when towbar is upright position or at freely down position, which increases much the safety when the dolly is running.
- *Heavy duty 76mm dia. roller.
- *E-shape spring loaded safe tow hitch.
- *Heavy duty frame with high quality steel and flux core MIG welding.
- *Easy maintenance jobs.
- *Hot dip galvanizing.

SPECIFICATION:

- *Overall dimensions (LxWxH): 3660mm x 3460mm x 560mm
- *Working flat dimensions(LxWxH):3460mm x 2660mm x 515mm
- *Capacity: 7000kgs
- *Tyres: Front 320-8,Rear 350x100 super elastic solid rubber tires 400-8 super solid rubber tires for optional
- *Weight: 1150kgs
- *Maximum towing speed:25km/h.





10FEET PALLET DOLLY





Model No.: HD-P011704

10FEET PALLET DOLLY

FEATURES:

- *ULD to handle: LD1/LD3,LD8 container, or any container and pallet with the bottom size 125"x96", 125"x88" and 108"x88".
- *125"side loading.
- *Front bearing turntable steering.
- *Brake works when towbar is upright position or at freely down position, which increase much the safety when the dolly is running.
- *Heavy duty 76mm dia. roller.
- *Lock holding safe tow hitch.(E-shape spring loaded safe tow hitch option)
- *Heavy duty frame with high quality steel and flux core MIG welding.
- *Easy maintenance jobs.
- *Hot dip galvanizing.

SPECIFICATION:

- *Overall dimensions (LxWxH): 5023mm x 2600mm x 571mm
- *Working flat dimensions(LxWxH):3300mm x 2600mm x 510mm
- *Capacity: 7000kgs
- *Tyres: 16x5-9 super elastic solid rubber tyres.
- *Weight: 1350kgs
- *Maximum towing speed:25km/h.





10FEET PALLET DOLLY





Model No.: HD-P011707

10FEET PALLET DOLLY

FEATURES:

- *ULD to handle: LD1/LD3,LD8 container, or any container and pallet with the bottom size 125"x96", 125"x88" and 108"x88".
- *96" side loading.
- *Front swivel castor steering.
- *Brake works when towbar is upright position or at freely down position, which increase much the safety when the dolly is running.
- *Heavy duty 76mm dia. roller.
- *E-shape spring loaded safe tow hitch.
- *Heavy duty frame with high quality steel and flux core MIG welding.
- *Easy maintenance jobs.
- *Hot dip galvanizing.

SPECIFICATION:

- *Overall dimensions (LxWxH): 4137x3460x560mm
- *Working flat dimensions(LxWxH): 3460x2610mmx518mm
- *Capacity: 7000kgs
- *Tyres: Front 320-8,Rear 350x100 super elastic solid rubber tyres. 400-8 super solid rubber tires for optional
- *Weight: 1150kgs
- *Maximum towing speed:25km/h.



Model No.: HD-P011708 10FEET CASTOR-BED PALLET DOLLY with Safety Cover



Model No.: HD-P011708 10FEET CASTOR-BED PALLET DOLLY with Safety Cover

FEATURES:

- *ULD to handle: LD1/LD3,LD8 container, or any container and pallet with the bottom size 125"x96", 125"x88"and 108"x88".
- *96" side loading or 125" side loading.
- *Heavy duty front swivel castor steering.
- *Brake works when towbar is upright position
- *Heavy duty castors bed, on which the pallet or container can rotate 360 degree.
- * Cover available for safety purpose.
- *E-shape spring loaded safe tow hitch.
- *Heavy duty frame with high quality steel and flux core MIG welding.
- *Easy maintenance jobs.
- *Hot dip galvanizing.

SPECIFICATION:

- *Overall dimensions (LxWxH): 4707mm x 2590mm x 513mm
- *Working flat dimensions(LxWxH): 3420mm x 2590mm x 513mm
- *Capacity: 7000kgs
- *Tyres: 400-8 super elastic solid rubber tyres.
- *Weight: 1108kgs
- *Maximum towing speed:25km/h.





10FEET PALLET DOLLY



Model No.: HD-P011709

10FEET PALLET DOLLY

FEATURES:

- *ULD to handle: LD1/LD3,LD8 container, or any container and pallet with the bottom size 125"x96", 125"x88"and 108"x88".
- *96" side loading.
- *Heavy duty front swivel castor steering.
- *Brake works when towbar is upright position or at freely down position, which increases much the safety when the dolly is running.
- *Heavy duty 76mm dia. roller.
- *E-shape spring loaded safe tow hitch.
- *Heavy duty frame with high quality steel and flux core MIG welding.
- *Easy maintenance jobs.
- *Hot dip galvanizing.

SPECIFICATION:

- *Overall dimensions (LxWxH): 4084mm x 3356mm x 560mm
- *Working flat dimensions(LxWxH): 3356mm x 2620mm x 518mm
- *Capacity: 7000kgs
- *Tyres: 400-8 super elastic solid rubber tyres.
- *Weight: 1275kgs
- *Maximum towing speed:25km/h.





10FEET PALLET DOLLY



Model No.: HD-P011710

10FEET PALLET DOLLY

FEATURES:

- *ULD to handle: LD1/LD3,LD8 container, or any container and pallet with the bottom size 125"x96", 125"x88"and 108"x88".
- *96" side loading.
- *Heavy duty front swivel castor steering.
- *Brake works when towbar is upright position or at freely down position, which increases much the safety when the dolly is running.
- *Heavy duty 76mm dia. roller.
- *E-shape spring loaded safe tow hitch.
- *Heavy duty frame with high quality steel and flux core MIG welding.
- *Easy maintenance jobs.
- *Hot dip galvanizing.

SPECIFICATION:

- *Overall dimensions (LxWxH): 4170mm x 3390mm x 598mm
- *Working flat dimensions(LxWxH): 3390mm x 2640mm x 518mm
- *Capacity: 7000kgs
- *Tyres: 400-8 super elastic solid rubber tyres.
- *Weight: 1460kgs
- *Maximum towing speed:25km/h.





10FEET PALLET DOLLY LD7 DOLLY



Model No.: HD-P011711

10FEET PALLET DOLLY LD7 DOLLY

FEATURES:

- * ULD to handle: any container and pallet with the bottom size 125"x96", 125"x88", or 108"x 88". (Stops for LD1/LD3, LD8 containers are for option)
- *125"side loading.
- *Heavy duty swivel castor steering.
- *Brake works when towbar is upright position or at freely down position, which increases much the safety when the dolly is running.
- *Heavy duty 76mm dia roller.
- *E-shape spring loaded safe tow hitch.
- *Heavy duty frame with high quality steel and flux core MIG welding.
- *Easy maintenance jobs.
- *Hot dip galvanizing.

SPECIFICATION:

- * Overall dimensions (LxWxH): 4898mm x 2650mm x 645mm
- * Woking flat dimensions(LxWxH):3400mm x 2650mm x 518mm
- * Capacity: 7000kgs
- * Tyres: 400-8 super elastic solid rubber tyres.
- * Weight: 1275kgs
- * Maximum towing speed:25km/h.



