

Model No.: HD-TG25A

Liquified Petroleum Gas Tractor



Model No.: HD-TG25A

Liquified Petroleum Gas Tractor

The HD-TG25A is a Liquefied gas -driven baggage tractor ; It features with low cost and enviromental friendly. It is widely used in airports, stations, warehouses, industrial and mining enterprises and other fields. It is in compliance with IATA AHM 910 ,IATA AHM 913,IATA AHM 915, IATA AHM925, GB4785-2007, GB7258-2017, MHT-6048-2008 requirements.

FEATURES:

- *Engine: GUANGQING GQ4Y /four-stroke, water-cooled
39/2800 Kw/rpm; 156/1800 N.m/rpm
- *Transmission: Okamura Y43300X;Automatic; 2 forward/1 backward (for optional)
- *Front axle: Spiral spring independent suspension with Telescopic Shock Absorber
- *Rear axle: Leaf spring suspension with Telescopic Shock Absorber
- *Steering: Hydraulic steering system.
- *Front brake: Hydraulic drum brake with vacuum booster.
- *Rear brake: Hydraulic disc brake with vacuum booster.
- *Electrical system: DC 12V

SPECIFICATIONS:

- *Overall dimensions (LxWxH): 3170x1440x1480mm (without cab and with Tow hitch)
3170x1440x2050mm (with cab and with Tow hitch)
- *Turning radius: 3000mm
- *Wheelbase: 1740mm
- *Track F/R: 1230mm/1170mm
- *Tow hitch height: 304.8mm/405mm
- *Ground clearance: 150mm
- *Self weight: Approx. 3400kgs (without cab)
- *Tyre F/R: 6.50-10-10PR / 28x9-15 14PR
- *Working temperature: -40℃ ~+65℃
- *Maximum pull: 25KN (20KN Available)
- *Cylinder Capacity: 2237cc
- * Optional: Single or Dual fuel available.

OPTIONAL FEATURES

Windshield, simple driving cab and sealed cab,air conditioning, hot air blower; custom-built traction pins, small loading platform ,monitoring and recording system,tool box and so on.

