

Model No.: HD-BT25A Baggage Tow Tractor



Model No.: HD-BT25A Baggage Tow Tractor

The HD-BT25A is a high performance and widely used baggage towing tractor to provide traction service for dolly and trailers in airports, stations, warehouses, industrial and mining enterprises and other fields. It is in compliance with IATA AHM 905 ,IATA AHM 910,IATA AHM 913 and GB1589, GB4785-2007,GB7258-2004 , MHT-6048-2008 requirements.

FEATURES:


- *Engine: Cummins QSF2.8;43kw/2500rpm;186Nm/1500rpm
Yanmar 4TNE98(Japan);43kw/2300rpm;196.3N.m/1700rpm (for optional)
- *Transmission: GRAZIANO PST2;Automatic;2 forward/1 backward
Okamura340;Automatic; 2 forward/1 backward (for optional)
- *Emission: EU Stage III
- *Front axle: Spiral spring independent suspension with Telescopic Shock Absorber
- *Rear axle: Leaf spring suspension with Telescopic Shock Absorber
- *Steering: Hydraulic steering system.
- *Front brake: Hydraulic drum brake with vacuum booster.
- *Rear brake: Hydraulic disc brake with vacuum booster.
- *Electrical system: DC 12V

SPECIFICATIONS:

- *Overall dimensions (LxWxH): 3000x1440x1450mm (without cab)
3000x1440x2000mm (with cab)
- *Turning radius: 2950mm
- *Wheelbase: 1600mm
- *Track F/R: 1230mm/1170mm
- *Tow hitch height: 304.8MM/405mm
- *Ground clearance: 150mm
- *Self weight: Approx. 3600kgs (without cab)
- *Tyre F/R: 6.50-10PR / 7.00-15PR
- *Working temperature: -40℃ ~+65℃
- *Maximum pull: 25KN

OPTIONAL FEATURES

Windshield, simple driving cab and sealed cab, air conditioning, hot air blower, custom-built traction pins, small loading platform ,monitoring and recording system,tool box and so on.



yummo



Since 1959

www.handlingyummo.com
info@handlingyummo.com